



Future-proof the way you work



Unified Cloud Connection

You only need to sign in once to connect to multiple cloud services, such as Microsoft Teams, from the MFP. Applications can also be easily downloaded from the cloud. Updates are clearly displayed, so you're always using the latest version of services.

Solid Security

The MFP has multiple levels of security to keep the device—and your precious data—secure. When booting up, the MFP checks for any anomalies in the BIOS firmware. If it finds a problem, it aborts the startup. If there are other firmware-related issues, the MFP will attempt recovery to protect the system.

Link Mobile Devices

Mobile devices installed with the Sharpdesk Mobile application can connect directly to the MFP for printing or downloading scanned data. The MFP can also be equipped with AirPrint and the Sharp Print Service Plugin. It's a smoother way to get the job done.

Wireless LAN Connection

The MFP works with the 5 GHz band. This ensures minimal radio interference and stable high-speed communications. The MFP also supports Wi-Fi Protected Setup™. This makes it easy to connect the MFP to a secure wireless LAN without having to enter an SSID and security key.

All the Needed Finishing Options

The MFP meets all common office needs with a variety of finishing options. Its folding unit handles various types of folds without taking up much space—it attaches to the MFP's paper output section. You get seamless output from printing to finishing.

smart business partner

10.1-Inch Full-Flat Touchscreen

With a variety of functions accessible via simple, intuitive icons, MFP operation is smooth and easy.

On-Screen System Information

The control panel shows the state of your MFP, displaying current operation and notifications for things like paper, toner, and maintenance.

High-Performance DSPF

The DSPF (duplex single pass feeder) scans both pages of two-sided documents in one pass—in batches of up to 300 sheets. With scanning speeds of up to 280 opm* (two-sided), the MFP is quick to finish even large jobs. A dedicated business card feeder on the DSPF scans batches of up to 150 cards.

Smart Scanning

Simply tap the Auto Set button and the MFP will automatically determine the optimal resolution, gradation, and compression rate for your scan jobs. It also automatically reorients pages right side up and corrects any skewed sheets.

Eco-Friendly Design

Despite its many functions, this MFP achieves superb energy efficiency. For example, the use of low-temperature-fusing toner results in vastly reduced energy consumption for the MFP.

Remote Firmware Updates


The MFP's firmware can be remotely updated—without the need for service operation—via a firmware update service. That way you're always using the latest system for your MFP.

PROFESSIONAL-QUALITY IN-LINE FINISHING OPTIONS


A range of finishing options work to automate time-consuming finishing tasks. Options are available to suit a variety of workplaces and applications.

| | | BP-FD10 Folding Unit | BP-FN11 Finisher | BP-FN13 Finisher | BP-FN13 Finisher | BP-FN14 Saddle Stitch Finisher | BP-FN14 Saddle Stitch Finisher | BP-FN15 Finisher | BP-FN15 Finisher | BP-FN16 Saddle Stitch Finisher | BP-FN16 Saddle Stitch Finisher |
|------------------|----------------------|-------------------------|---------------------|---------------------|-------------------------|--------------------------------------|--------------------------------------|---------------------|-------------------------|--------------------------------------|--------------------------------------|
| | | | | | + | | + | | + | | + |
| | | | | | BP-FD10 Folding Unit | | BP-FD10 Folding Unit | | BP-FD10 Folding Unit | | BP-FD10 Folding Unit |
| Features | Stapling | | √ | ✓ | √ | √ | ✓ | √ | ✓ | √ | ✓ |
| | Stapleless stapling | | \checkmark | | | | | \checkmark | √ | √ | √ |
| | Manual stapling | | \checkmark | | | | | √ | √ | √ | √ |
| | Punching*1 | | \checkmark | √ | √ | \checkmark | √ | √ | √ | √ | √ |
| | Saddle folding | | | | | \checkmark | √ | | | √ | √ |
| | Saddle stitching | | | | | \checkmark | √ | | | √ | √ |
| | Half-folding | ✓ | | | √ | | √ | | √ | | √ |
| | Z-folding | √ | | | √ | | √ | | √ | | √ |
| | Z-folding + Stapling | | | | | | | | √ | | √ |
| | C-folding | √ | | | ✓ | | √ | | √ | | √ |
| | Accordion folding | √ | | | √ | | ✓ | | √ | | √ |
| | | | | | 1 | | | | | | |
| Paper capacity*2 | Finisher trays*3 | - | 500 sheets | 1,250 sheets | 1,250 sheets | 1,250 sheets | 1,250 sheets | 3,250 sheets | 3,250 sheets | 3,250 sheets | 3,250 sheets |
| | Folding unit tray | 200 sheets | - | - | 100 sheets | - | 100 sheets | - | 100 sheets | - | 100 sheets |

*1: Requires optional punch module. *2: A4, 80 g/m². *3: Max. paper capacity of the finisher including the top tray.



SYSTEM CONFIGURATION



SPECIFICATIONS FOR OPTIONAL EQUIPMENT

MX-TR20 N Job Separator Tray

| Paper size | SRA3 to A6*1 | |
|-----------------------------------|--------------|--|
| Paper capacity | 100 sheets | |
| | | |
| BP-TR12 Exit Tray Unit | | |
| BP-TR12 Exit Tray Unit Paper size | SRA3 to A6*1 | |

BP-FN11 Finisher

| Paper size | Non offset | SRA3 to A6*1 |
|-------------------|------------------------|---|
| | Offset/staple | A3 to B5*2 |
| | Stapleless staple | A3 to B5*3 |
| Paper capacity | Non offset | 500 sheets (A4, B5, A5) |
| | | 250 sheets (SRA3, A3W, SRA4, A3, B4, A6*1) |
| | Offset | 500 sheets (A4, B5 ^{*2}), 250 sheets (A3, B4) |
| | Staple | 30 sets or 500 sheets (A4, B5*2) |
| | | 30 sets or 250 sheets (A3, B4) |
| | Stapleless staple | 30 sets |
| Stapling capacity | Staple | 50 sheets (A4, B5*2), 30 sheets (A3, B4) |
| | Stapleless staple | 10 sheets*4 (A4*2, B5*2), 5 sheets*5 (A3, B4) |
| | Manual staple | Total paper thickness 4 mm or less (40 sheets) |
| Staple position | Staple mode | 3 locations (front, rear, or 2-point stapling) |
| | Stapleless staple mode | 1 location (rear) |
| | Manual staple mode | 1 location |

BP-FN13 Finisher

| Paper size | Non offset | SRA3 to A6*1 |
|-----------------|----------------------------|--|
| | Offset | A3W to A5 |
| | Staple | A3W to B5 |
| Paper capacity | Finisher tray (Non offset) | 1,000 sheets (A4*2) |
| | | 500 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5, A5, A6*1) |
| | (Offset) | 1,000 sheets (A4*2) |
| | | 500 sheets (A3W, A3, B4, A4*1, B5, A5) |
| | (Staple) | 100 sets or 1,000 sheets (A4*2) |
| | | 50 sets or 500 sheets (A3W, A3, B4, A4*1, B5) |
| | Top tray | 250 sheets (A4, B5, A5, A6*1) |
| | | 50 sheets (SRA3, A3W, SRA4, A3, B4) |
| Stapling capaci | ty | 50 sheets (A4, B5), 30 sheets (A3W, A3, B4) |
| Staple position | | 3 locations (front, rear, or 2-point stapling) |

BP-FN14 Saddle Stitch Finisher

| Paper size | Non offset | SRA3 to A6*1 |
|-----------------|----------------------------|--|
| | Offset | A3W to A5 |
| | Staple | A3W to B5 |
| Paper capacity | Finisher tray (Non offset) | 1,000 sheets (A4*2) |
| | | 500 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5, A5, A6*1) |
| | (Offset) | 1,000 sheets (A4*2) |
| | | 500 sheets (A3W, A3, B4, A4*1, B5, A5) |
| | (Staple) | 100 sets or 1,000 sheets (A4*2) |
| | | 50 sets or 500 sheets (A3W, A3, B4, A4*1, B5) |
| | Top tray | 250 sheets (A4, B5, A5, A6*1) |
| | | 50 sheets (SRA3, A3W, SRA4, A3, B4) |
| | Saddle stitch tray | 7 sets of 11–15 sheets, 10 sets of 6–10 sheets, |
| | | 20 sets of 1–5 sheets |
| Stapling capaci | ty | 50 sheets (A4, B5), 30 sheets (A3W, A3, B4) |
| Staple position | | 3 locations (front, rear, or 2-point stapling) |

BP-FN15 Finisher

| Paper size | Non offset | SRA3 to A6*1 |
|-------------------|----------------------------|---|
| | Offset/staple | A3 to B5*2 |
| | Stapleless staple | A3, A4*2 |
| Paper capacity | Finisher tray (Non offset) | 3,000 sheets (A4*², B5*²) |
| | | 1,500 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5*1, A5) |
| | | 750 sheets (A6*1) |
| | (Offset) | 3,000 sheets (A4*², B5*²) |
| | | 1,500 sheets (A3, B4, A4*1) |
| | (Staple) | 200 sets or 3,000 sheets (A4*2, B5*2) |
| | | 100 sets or 1,500 sheets (A3, B4, A4*1) |
| | (Stapleless staple) | 200 sets (A4*2), 100 sets (A3) |
| | Top tray | 250 sheets (A4* ² , B5* ² , A5) |
| | | 125 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5*1) |
| Stapling capacity | Staple | 65 sheets (A4* ² , B5* ²), 30 sheets (A3, B4, A4* ¹) |
| | Stapleless staple | 10 sheets*4 (A4*2), 5 sheets*5 (A3) |
| | Manual staple | Total paper thickness 9 mm or less (65 sheets) |
| Staple position | Staple mode | 3 locations (front, rear, or 2-point stapling) |
| | Stapleless staple mode | 1 location (rear) |
| | Manual staple mode | 1 location |

BP-FN16 Saddle Stitch Finisher

| DF-FN10 Jau | ale Stitti Fillisilei | |
|-------------------|----------------------------|--|
| Paper size | Non offset | SRA3 to A6*1 |
| | Offset/staple | A3 to B5*2 |
| | Stapleless staple | A3, A4*2 |
| Paper capacity | Finisher tray (Non offset) | 3,000 sheets (A4*², B5*²) |
| | | 1,500 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5*1, A5) |
| | | 750 sheets (A6*1) |
| | (Offset) | 3,000 sheets (A4*2, B5*2) |
| | | 1,500 sheets (A3, B4, A4*1) |
| | (Staple) | 200 sets or 3,000 sheets (A4*2, B5*2) |
| | | 100 sets or 1,500 sheets (A3, B4, A4*1) |
| | (Stapleless staple) | 200 sets (A4*2), 100 sets (A3) |
| | Top tray | 250 sheets (A4* ² , B5* ² , A5) |
| | | 125 sheets (SRA3, A3W, SRA4, A3, B4, A4*1, B5*1) |
| | Saddle stitch tray | 10 sets of 11–20 sheets, 15 sets of 6–10 sheets, |
| | | 25 sets of 1–5 sheets |
| Stapling capacity | Staple | 65 sheets (A4*2, B5*2), 30 sheets (A3, B4, A4*1) |
| | Stapleless staple | 10 sheets*4 (A4*2), 5 sheets*5 (A3) |
| | Manual staple | Total paper thickness 9 mm or less (65 sheets) |
| Staple position | Staple mode | 3 locations (front, rear, or 2-point stapling) |
| | Stapleless staple mode | 1 location (rear) |
| | Manual staple mode | 1 location |

Punch Modules

| Model name | For BP-FN11 | MX-PN14B*6 | MX-PN14C*7 | MX-PN14D |
|----------------|------------------|------------|-------------------|----------|
| | For BP-FN13/FN14 | MX-PN15B*6 | MX-PN15C*7 | MX-PN15D |
| | For BP-FN15/FN16 | MX-PN16B*6 | MX-PN16C*7 | MX-PN16D |
| Number of hole | S | 2 or 3 | 2 or 4 | 4 (wide) |
| Paper weight | | | 55 to 256 g/m² *8 | 8 |

BP-FD10 Folding Unit

| Folding mode | | Z-fold, C-fold, Accordion-fold, Half-fold |
|----------------|-------------------|---|
| Paper size | Z-/Half-fold | A3, B4, A4*1 |
| | C-/Accordion-fold | A3, A4*1 |
| Paper capacity | Not folded | 200 sheets |
| | Folded | 20 sheets*9 |

BP-DE12 Stand with 550-Sheet Paper Drawer

| Paper size | SRA3 to A5*1 |
|----------------|--------------|
| Paper capacity | 550 sheets |

BP-DE13 Stand with 2 x 550-Sheet Paper Drawer

| Paper size | Upper and lower tray | SRA3 to A5*1 |
|----------------|----------------------|-----------------|
| Paper capacity | Upper and lower tray | 550 sheets each |

BP-DE14 Stand with 3 x 550-Sheet Paper Drawer

| Paper size | Upper/middle/lower tray | SRA3 to A5*1 |
|----------------|-------------------------|-----------------|
| Paper capacity | Upper/middle/lower tray | 550 sheets each |

BP-DE15 Stand with 550 + 2,100-Sheet Paper Drawer

| Paper size | Upper tray | SRA3 to A5*1 |
|----------------|------------------|-------------------------------------|
| | Lower right tray | A4* ² , B5* ² |
| | Lower left tray | A4*2 |
| Paper capacity | Upper tray | 550 sheets |
| | Lower right tray | 900 sheets |
| | Lower left tray | 1,200 sheets |

BP-LC10 Large Capacity Tray

| Paper size | A4*2, B5*2 |
|----------------|--------------|
| Paper capacity | 3,000 sheets |

MX-LT10 Long Paper Feeding Tray

| Paper size | Width | 90 to 320 mm |
|----------------|--------|-----------------|
| | Length | 458 to 1,300 mm |
| Paper capacity | | 1 sheet |

Note: All specifications relating to paper capacity refer to 80 $g/m^{\rm 2}$ paper.

*1: Short-edge feeding. *2: Long-edge feeding. *3: Long-edge feeding for A4 and B5 paper. *4: Guaranteed stapleable weight is up to 64 g/m² (8 sheets up to 81.4 g/m² and 6 sheets up to 105 g/m²). *5: Guaranteed stapleable weight is up to 64 g/m² (4 sheets up to 81.4 g/m² and 3 sheets up to 105 g/m²). *6: Accepts North American paper sizes. *7: Accepts ISO-standard paper sizes. *8: Guaranteed punchable weight is 60 to 128 g/m². *9: When used with a finisher, 30 Z- or half-folded sheets (A3 and B4). These sheets are ejected from the finisher.

SPECIFICATIONS

| Genera |
|--------|
| |

| Type Engine speed | Desktop A4*1: Max. 31 ppm A3: Max. 15 ppm SRA3: Max. 14 ppm | |
|----------------------------|--|-------------------------|
| Control panel display | 10.1-inch colour LCD touchscreen | |
| Paper size | Max. SRA3, min. A6*2 | |
| Paper capacity | Standard: 650 sheets | |
| (80 g/m²) | (550-sheet tray and 100-sheet bypass t | ray) |
| | Maximum: 6,300 sheets | |
| | (650 sheets & optional 550 + 2,100-sheet tra | y and 3,000-sheet tray) |
| Paper weight | Tray: 60 g/m ² to 300 g/m ² | |
| | Bypass tray: 55 g/m ² to 300 g/m ² | |
| Warm-up time* ³ | 18 sec.*4 | |
| Memory | Standard: 5 GB (copy/print shared) | 256 GB SSD*5 |
| | Option: 512 GB*5*6 | |
| Power requirements | Rated local AC voltage ±10%, 50/60 Hz | |
| Power consumption | Max. 1.84 kW (220 V to 240 V) | |
| Dimensions (W x D x H)*7 | 609 x 662 x 860 mm | |
| Weight (approx.) | 85 kg | |
| | | |

Copier

| Original paper size First copy time* ⁸ Continuous copy | Max. A3 Colour: 7.6 sec. Max. 9.999 copies | B/W: 5.6 sec. |
|---|--|------------------------------|
| Resolution | Scan (colour): 600 x 600 dpi | |
| | Scan (B/W): 600 x 600 dpi, 60 | 0 x 400 dpi, 600 x 300 dpi*9 |
| | Print (colour): 600 x 600 dpi, | 9,600 (equivalent) x 600 dpi |
| | (depending on copy mode) | |
| | Print (B/W): 1,200 x 1,200 dpi | , 600 x 600 dpi, |
| | 9,600 (equivalent) x 600 dpi (| depending on copy mode) |
| Gradation | Equivalent to 256 levels | |
| Zoom range | 25% to 400% (25% to 200% u | sing DSPF) in 1% increments |
| Preset copy ratios | 10 ratios (5R/5E) | |

Scanner

| Scan method | Push scan (via control panel) |
|---------------------------|--|
| | Pull scan (TWAIN-compliant application) |
| Scan speed ^{*10} | One-sided: Max. 140 originals/min. |
| (colour & B/W) | Two-sided: Max. 280 originals/min. |
| Resolution | Push scan: 100, 150, 200, 300, 400, 600 dpi |
| | Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi |
| | 50 dpi to 9,600 dpi via user setting*11 |
| File formats | TIFF, PDF, PDF/A-1a, PDF/A-1b, encrypted PDF, XPS, |
| | compact PDF ^{*12} , JPEG ^{*12} , searchable PDF, OOXML |
| | (pptx, xlsx, docx), text (TXT [UTF-8]), rich text (RTF) |
| Scan destinations | Email/desktop*13/FTP server/network folder (SMB)/ |
| | USB drive/local drive |
| | |

*1: Long-edge feeding.

- *2. Only short-edge feeding can be used with A6 paper.
- *3: In a standard measurement environment. May vary depending on operating conditions and environment.
- *4: When starting the MFP via the power button. 29 seconds when starting via the main power switch.
- *5: Storage capacity depends on procurement and sourcing status
- Replacing the standard-equipped SSD with the optional BP-SD10 increases storage capacity to 512 GB. *6: *7.
- Including protuberances
- Long-edge feeding of A4 sheets from 1st paper tray, using document glass, without Auto Colour *8: Selection and Auto Colour mode, MFP in fully ready condition. May vary depending on operating conditions and environment.
- *9: Not available when using document glass.
 *10: Based on Sharp's A4 standard chart, using document feeder and long-edge feeding. Using factory default settings with Auto Colour Selection off. Scan speed will vary depending on the type of document and the scan settings.
- *11: Resolution will vary depending on the size of the scanned area. *12: Colour/greyscale only.
- *13: Requires Network Scanner Tool Lite. *14: Storage capacity will vary depending on the type of document and the scan settings.
- *15: Some features require optional equipment.
 *16: Based on Sharp's standard chart with approx. 700 characters (A4 long-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression.

Document Filing

| Document filing capacity ^{*14} Stored jobs ^{*15} Storage folders | Main a Quick Copy, Quick (max. |
|---|--|
| Drintor | _ |

and custom folders: 20,000 pages or 3,000 files file folder: 10,000 pages or 1,000 files print, scan, fax file folder, main folder, custom folder 1,000 folders)


| Resolution Interface | 1,200 x 1,200 dpi, 600 x 600 dpi, 9,600 (equivalent) x 600 dpi USB 2.0 (host, high-speed), USB 3.0 (host, super speed), 10Base-T/100Base-TX/100Base-T. |
|-------------------------|--|
| | wireless LAN (IEEE 802.11 a/b/g/n/ac) |
| Supported OS | Windows Server 2012, Windows Server 2012 R2, |
| | Windows Server 2016, Windows Server 2019, |
| | Windows Server 2022, Windows 8.1, Windows 10, Windows 11, |
| | Mac OS 10.10, 10.11, 10.12, 10.13, 10.14, 10.15, 11, 12 |
| Network protocols | TCP/IP |
| Printing protocols | LPR, Raw TCP (port 9100), POP3 (email printing), HTTP, |
| | FTP for downloading print files, IPP, IPP Everywhere, SMB, WSD |
| PDL | PCL 6 emulation, Adobe PostScript 3 |
| Available fonts | 80 fonts for PCL, 139 fonts for Adobe PostScript 3 |

Facsimile (requires optional BP-FX11)

| Compression method | MH/MR/MMR/JBIG |
|-------------------------|---|
| Communication protocol | Super G3/G3 |
| Transmission time | Less than 3 seconds ^{*16} |
| Modem speed | 33,600 bps to 2,400 bps with automatic fallback |
| Transmission resolution | From Standard (203.2 x 97.8 dpi) to |
| | Ultra Fine (406.4 x 391 dpi) |
| Recording size | A3 to A5 |
| Memory | 4 GB (built-in) |
| Greyscale levels | Equivalent to 256 levels |

Design and specifications are subject to change without prior notice

· Microsoft Teams, Windows, and Windows Server are trademarks of the Microsoft group of Companies. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. Wi-Fi Protected Setup is a trademark of Wi-Fi Alliance®. PCL is a registered trademark of Hewlett-Packard Company. Adobe and PostScript are either registered trademarks or trademarks of Adobe in the US and/or other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.



* 1,648 mm when finisher tray and exit tray are extended.

Shown with optional equipment.

Distributed by:

SHARP